



## FAST, EASY & SAFE TO APPLY

## BONDED/HOT MELT STRAPPING

Bonded strapping, otherwise referred to as hot melt strapping, has many advantages over conventional manually applied products such as steel straps, metal banding, rope, plastic straps and stretch film. Compared to these products bonded strapping is applied in a faster, safer and more cost effective way.

The bonded strapping can be joined by a simple knot or used in combination with buckles, tools and tensioners, providing the most dependable joining systems. The strapping can be tensioned using manual or pneumatic tension tools.

QUALITY ASSURED



## FEATURES & BENEFITS

- Faster and safer to apply
- Cost-effective
- Gentle on delicate edges and surfaces
- Dynamic load movement is absorbed by the elasticity of the strapping.
- Can be custom printed on
- Weatherproof and UV resistant
- Can be joined by a simple knot or used in combination with buckles, tools and tensioners
- Hot melt lamination provides for controlled uncoiling
- Superior system strength when used with Narrowtex "Extra Grip" phosphate buckles



## CUSTOMISATIONS

Bonded strapping can be printed in various colours. This is often requested by our clients to indicate break strength as well as promote their brand identity.

## INDUSTRY APPLICATIONS

- AGRICULTURE
- ABATTOIRS (MEAT INDUSTRY)
- BALE PRESS



### CONTACT US

Tel: +27 36 352 3108

Narrowtex@narrowtex.co.za | www.narrowtex.com

254 Loskop Road,  
Estcourt, 3310  
South Africa

# NARROWTEX

NARROWTEX IS PART OF THE NTX GROUP, A SUBSIDIARY OF SA BIAS INDUSTRIES PTY LTD

## BONDED/HOT MELT STRAPPING PRODUCTS

STOCK CODE	WIDTH (MM)	WIDTH (INCHES)	LINEAR BREAKING STRENGTH (KG)	LINEAR BREAKING STRENGTH (POUNDS)	COIL SIZE (METRES)	COIL SIZE (FEET)	COILS PER PALLET
BN 6-145	6	1/4	145	319	1800	5905	36
BN 9-225	9	3/8	225	495	1600	5249	36
BN 9-275	9	3/8	275	605	1600	5249	36
BN 13-275	13	1/2	275	605	1100	3609	36
BN 13-325	13	1/2	325	715	1200	3937	36
BN 13-370	13	1/2	370	814	1100	3609	36
BN 16-350	16	5/8	350	770	1000	3280	36
BN 16-370	16	5/8	370	814	1000	3280	36
BN 16-450	16	5/8	450	990	850	2788	36
BN 19-450	19	3/4	450	990	600	1969	36
BN 19-520	19	3/4	520	1144	600	1969	36
BN 19 - 640	19	3/4	640	1408	600	1969	36

\*ALL BREAKS ARE NOMINAL +/- 5%

Please contact us for any custom packing, size or other specific requirements